

LED Work light

SM-4016-SFE



| Function and performance | Parameters |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Item no. | SM-4016-SFE |
| Dimension | 103.8*103.8(131.2)*47.3(58.6)mm ,Including bracket size W4.08" x D4.08" x H1.86 Inch |
| Working voltage | 12 ~ 48VDC |
| Theoretical power | 16W; OSRAM 1W*16Pcs |
| Color temperature | 5500~6500 K |
| Luminous flux | 1200±200 lm |
| Working temperature | -40 °C~ +65°C |
| Waterproof and Dustproof | IP67 |
| Corrosion resistance of surface | Cross-cut adhesion test 0 grade |
| Neutral salt spray test | 126H |
| EMC | EN50498 |
| Light attenuation | Light attenuation ≤5% , working <8000h |
| Warranty | 1 year |
| Wiring method | a.Embedded DT terminal connector with open wire, wire length 150mm (DT Terminal connector DT04-2P) b. Direct wiring, wire length 150mm |
| Installation method | Bracket stand, install with Screw M10*25 (304SUS) |
| Rear housing | Aluminium alloy-ADC12; Matte black |
| Package | White box + Bubble bag |
| Packeging | 1set/Box, 24units / Carton |