



LED Work Light

SM-4027-RFG



Function and performance	Parameters
Item No.	SM-4027-RFG
Dimension	Φ116*146.5*51.6(42.6) mm, (including bracket size) R4.57" X D5.77" X H2.03" Inch
Theoretical power/ Color temperature	27W, LED- 3W*9Pcs, 5700~6500 K, White color
Working voltage	12~36V DC
Luminous flux	> 1700 LM, Light efficiency > 90LM/W
Beam angle	50%(H,V)= (30°,30°) Flood
Working temperature	-40°C~ +85°C
Waterproof and Dustproof	IP67
Over voltage protection	36VDC, 60S
Reverse polarity protection	36VDC, 60Min
EMC	CISPR-25 Class3
Vibration strength	30g
Transient shock	50g
Life span	> 30000h
Connection	Embedded DT terminal connector with wire harness, wire length 250mm (Terminal connector DT04-2P) (Red: positive electrode +, Black: negative electrode -)
Installation method	Bracket stand screw fixture, screw M10*20
Application	Engineering vehicle、special vehicle
Packaging	White color box. 1set/box, 20sets/carton (10 Pairs)

SAMMOON VEHICLE LIGHTING TECHNOLOGY CO., LTD

Add: 2nd-3rd Section, 4th Floor, Building 1, Hongxing Real Estate, No. 6, Foluo Road, Luocun, Shishan Town, Nanhai District, Foshan City, Guangdong province, China