



Headlight of Commercial vehicle

SM-5060-SDD

Function and performance	Parameters
Item No.	SM-5060-SDD
Dimension	L167.2 * W107.4 * T81mm L6.58" x W4.23" x T3.19" Inch
Working voltage	12-36V DC
Theoretical power /Actual power	60 W / 50W
Function /Theoretical power /Color temperature /Light color	High beam light: 27W, 9W*3pcs,5700~6500K, White color, Actual power: 22W, Current: 700mh Low beam light: 27W, 9W*3pcs,5700~6500K, White color, Actual power: 22W, Current: 700mh
Luminous flux	2800LM±15% High beam 1500lm±15%, Low beam 1300lm±15%,
Over voltage protection	36VDC, 60min
Reverse polarity protection	36VDC, 1Min
Life span	25000h Light attenuation < 5% for working 1000h; Light attenuation < 10% for working 8000h
Vibration&shock resistance	JB/T-7159-2007
Weather resistance	GB/T 10485-2007
Connection	Integrated DT Connector with wire harness, L300mm
Installation method	Bracket stand, screw fixture 2-M8
Application	Truck、 Engineering vehicle、 Special vehicle, front lighting function
Packaging	White color box. 1 set/box, 12sets/ carton (6 Pairs)