

Front Signal light of Agricultural machinery



Item no. SM-6018-OSL-A/B

Function & performance	Parameters
Function	Front Turn signals (amber) + Front Position light (White)
Dimension	L153.5(171.5) * W106 * T69 mm L6.04" x W4.17" x T2.71" Inch
Working voltage	12V DC / 24VDC (Optional)
Rated power	9.2 W
Led lamp chip	SMD 1W*7PCS (Color temperature 3000K) SMD 0.2W*11PCS (Color temperature 5700~6500K)
Working temperature	-40°C ~ +65°C
Regulation	The Light Distribution Performance of front position lamp shall meet the requirements of GB 5920 < GB 5920-2008 Photometric Performance of front position lamp, rear position lamp, clearance lamp and brake lamp of automobile and trailer lamp. The Light Distribution Performance of front turn signal lamps shall meet the requirements of GB / T 17509 < Photometric Performance of turn signal lamps of automobiles and trailers >
Waterproof and Dustproof	IP65
Life span	> 25000h
Wiring method	Direct wiring, wire length 1300mm, Connector 0447301 RED: positive electrode (+), BLACK: negative electrode (-);
Installation method	Built-in install, Embedded 2-M5*45 screw, the distance between two mounting holes is 500mm. (Wrapped with PVC flame retardant sleeve)
Application	Construction machinery、 Special vehicle、 Agricultural machinery
Packaging	White color box, 1set/box, 12sets/carton (6 Pairs)