



LED Work light

SM-6018-SWA



Function and performance	Parameters
Item no.	SM-6018-SWA
Dimension	L200*W50*T45 (54) W7.87" x D1.97" x H1.77" Inch
Working voltage	12-36V DC / 36 VDC (Optional)
Led lamp chip	LatticePower HF-4W (LED -3W*6Pcs)
Color temperature	5700~6500K
Theoretical power	18W;
Luminous flux (stable)	≥2200 LM
Working temperature	-40 ~ +85°C
Corrosion resistance of surface	Cross-cut test 0 grade, Neutral salt spray test 126H
Waterproof and Dustproof	IP67
EMC	CISPR-25, CLASS-3 & ECE-R10
Life span	25000h, Light attenuation≤10% when working more than 8000h
Wiring method	Direct wiring, (Standard) L250mm; or Adopt DT terminal connector,DT04-2P, Optional
Install method	Bracket stand, install with Screw M6*25,The distance between two holes are 177±1mm.
Application	Construction machinery and agricultural equipment
Packaging	Colour box, 2pairs/Box, 10 pairs/Carton

SAMMOON VEHICLE LIGHTING TECHNOLOGY CO., LTD

Add: 2nd-3rd Section, 4th Floor, Building 1, Hongxing Real Estate, No. 6, Foluo Road, Luocun, Shishan Town, Nanhai District, Foshan City, Guangdong province, China