

Front combined lamp of Agricultural machinery



Item no. SM-6023-OSL-A

Function & performance	Parameters
Function	Front Turn signals (amber) +Front Position light +Floor light (White)
Dimension	L153.5(205.5) * W106 * T69 mm L6.04" x W4.17 " x T2.71" Inch
Working voltage	12V DC / 24VDC (Optional)
Rated power	22W (7W+ 10W + 5W) , Actual Power 18W
Led lamp chip	Front Turn signals: SMD 1W*7PCS (Amber, Color temperature conform to CIE1931) Front Position light: SMD 1W*10PCS (White, Color temperature conform to CIE1931) Floor light: SMD 5W*1PCS (White, Color temperature conform to CIE1931)
Working temperature	-40°C ~ +65°C
Regulation	light distribution performance of front Position light meet ECE-R7, ECE-R6
Waterproof and Dustproof	IP65
Life span	> 25000h
Wiring method	Direct wiring, wire length 1300mm, Connector 0447301 RED: positive electrode (+), BLACK: negative electrode (-);
Installation method	Built-in install, Embedded 2-M5*70 screw, the distance between two mounting holes is 50mm.
Application	Construction machinery、 Special vehicle、 Agricultural machinery
Packaging	White color box, 1set/box, 12sets/carton (6 Pairs Per Carton)