

LED Work Light

SM-6032-RFA



Function and performance	Parameters
Item No.	SM-6032-RFA
Dimension	141*124.5*60.2 (69.2)mm W5.55" x D4.9" x H2.37" Inch
Working voltage	12 ~ 48V DC
Theoretical power/ Actual power	32W / 18 ±1.5W (4W*8Pcs)
Color temperature	5700~6500 K
Luminous efficiency	≥75 lm/W
Luminous flux	≥1300 LM,
Working temperature	-40℃ ~ +85℃
Beam angle	H55° ,V45° Flood
Waterproof and Dustproof	IP67
Corrosion resistance of surface	Neutral salt spray test 126h
Over voltage protection	48VDC, 60Min
Reverse polarity protection	48VDC, 1Min
Vibration strength	GB/T 2423.10-2008 15G
Life span	25000h, Light attenuation < 10%, working 8000h
Weather resistance	GB/T 10485-2007
Connection	Integrated DT Connector with open wires, L300mm, DT04-2P (Red: positive electrode +, Black: negative electrode -)
Installation method	Bracket stand, screw fixture, screw M10
Application	Engineering vehicle、 Agriculture machinery、 Mine machinery
Packaging	White color box. 1set/box, 24sets/carton (12 Pairs)