

Headlight of Commercial vehicle and Mine Truck

SM-7050-SDC



Function and performance	Parameters
Item No.	SM-7050-SDC
Dimension	L197.5 * W138.9 * T94 mm L7.77" x W5.47" x T3.7" Inch
Working voltage / Power	12-32V DC /50W
Function/ Theoretical power/ Color temperature/ Light color	High beam light 20W (LED 2Pcs*10W), 5000±300K, White color. Low beam light 20W (LED1Pcs*20W), 4800K±300K,White color, Turn signals 4.5W (LED 3pcs*1.5W),3000K±300K,Amber, Front position light 3W (LED 3pcs*1W),5000K±300K,White
Luminous flux	2100LM±15%
Working temperature	-40°C- +85°C
Waterproof and Dustproof	IP67
Over voltage protection	32VDC, 60S
Reverse polarity protection	32VDC, 60Min
EMC	ECE-R10, CISPR-25 Class 3
Vibration strength	15G, 25Hz~110Hz sweep frequency
Life span	> 25000h
Wiring method /Connection	Direct wiring, wire length 200mm
Installation method	Built-in install, fixture with screw 2-M8*20, Distance =od two mounting holes in width side 120mm, Length side 154mm
Application	Truck, Engineering vehicle, Special vehicle, Agriculture machinery
Packaging	White color box. 1unit/box, 12 sets/carton (6Pairs)