



SPECIFICATION				
Effective power	25±3W			
Luminous flux	2600±300LM			
Color temperature	5000~6000K			
EMC	CISPR 25 CLASS 3			
Operating temperature	-40°C ~ +85°C			
Operating voltage	9~36V DC			
Reverse connection protection	9~36V DC			
Vibration	15G, 25-55Hz, sweep frequency			
Corrosion	Neutral salt spray 126H			
Transient impact	76V, 20ms			
Beam angle	flood			
Ingress protection	IP67			
Surface treatment	powder spray			
Connector	builtin DT04-2P			
Lifespan	3000H			
Camera	Voltage	9~36V DC	Power	≤1W
	Sensor	1/3 color CMOS	Signal	AHD
	System	PAL	Resolution	1280*720P
	Frame	720p@25fps/30fps	Minimum luminance	≥0.1Lux
	Signal noise ratio	37.2dB	Visual angle (H, V)	125°, 70°

Part No.		SM-CA4050-RFA			
Name	Date	Version	V1	PROJECT	
Design		Material		Ratio	1:1
Revision	Revision date	Revision mark	Draw	Surface treatment	Net Weight
Revision Record			Audit	佛山市三目汽车照明科技有限公司	
ERP	Drawing No.	Approve	SAMMOON VEHICLE LIGHTING TECHNOLOGY CO., LTD		