


## Rear combination light

Item no. SM-LG-8024B-L  
SM-LG-8024B-R



Function & performance	Parameters
Item no.	SM-LG-8024B-L SM-LG-8024B-R
Dimension:	L192 * W97.5 * T27.5mm / L7.55" x W3.83" x T1.08" Inch (not including the external part of M5 bolt 16.5mm)
Working voltage:	24V DC / 12VDC (Single voltage)
Rated power:	31W
Function: (Led lamp chip)	<p><b>Parking light:</b> 1W*8Pcs, Red color, (share the Led lamp chip of stop light)</p> <p><b>Stop light:</b> 1W*8Pcs, Red color (share the Led lamp chip of Parking light);</p> <p><b>Turn signals:</b> 1W*8Pcs, Amber color (Color temperature 1700K);</p> <p><b>Reversing light:</b> 1W *6Pcs, White color (Color temperature 5700-6500K);</p>
Color temperature:	<p>Turn signals light: 1700 K, Amber light</p> <p>Reversing light: 6000K, White light</p> <p>Parking light &amp; stop light: 5000K, Red light (Parking light &amp; stop light: Red light)</p>
Working temperature:	-40°C ~ +65°C
Waterproof and Dustproof:	IP67
Life span:	> 25000h
Mounting method:	Built-in, fixture with screw M5 bolt, Two mounting hole' s distance are 107mm, hole R5
Connection:	Direct wiring, red and black wire, wire standard length:250mm
Application:	Engineering vehicle、Agricultural equipment、Special vehicle
Packaging:	White color box, 2set/box, 12sets/carton (6 Pairs)