



# Front Combination Signal light

Item no. SM-SY4014-A

Function & performance	Parameters
Item no.	<b>SM-SY4014-A</b>
Function	<b>Front Turn signals / Front Position light</b>
Dimension	<b>L105.1 * W81.1 * T28.2 (36.7) mm</b> <b>L4.14" x W3.19" x T1.11" Inch</b>
Working voltage	24V DC
Theoretical power/ Actual power Power	11W <b>Front Turn signals:</b> 8*1W 3000-3500 Amber color, Actual Power: 4W <b>Front Position light:</b> 6*0.5W 5700-6500K, White color, Actual power: 0.5W
Working temperature	-40°C ~ +65°C
Waterproof and Dustproof	IP65
Corrosion resistance of surface	Neutral salt spray test 76H
Withstand voltage test	28VDC, 60Min
Reverse polarity protection	28VDC, 1Min
Vibration strength	6G
Life span	25000h, Light attenuation < 10% working for 8000h
Regulation	Turn signals: ECE R6; Position light: ECE R7
Weather resistance	GB/T 10485-2007
Wiring method	Direct wiring, wire length 200mm, RED: positive electrode (+), BLACK: negative electrode (-);
Installation method	Built-in install, mounting screw with 2-M4*10 bolt
Application	Engineering vehicle、Agriculture machinery、 Mine machinery
Packaging	White color box, 1set/box, 20sets/carton (10 Pairs)