

Rear combination light



Item no. SM-ZJTK-D-3B

Function and performance	Parameters
Item no.	SM-ZJTK-D-3B
Dimension	L420 * W140 * T26.1mm L16.54" x W5.51" x T1.03" Inch
Function	Turn signals (Yellow) Stop light / Position light (Red) Reversing light (White)
Led lamp chip	1.2W*7PCS LED
Components	Transparent housing: PC; Mounting plate: Q235A iron plate, Powder coating black of the surface.
Working voltage	24V DC
Theoretical power	8.4W+8.4W+8.4W, 25.2W
Actual power	Rear Turn signals: $3\pm 0.3W$; Rear Position light: $0.5\pm 0.2W$; Reversing light : $2.5\pm 0.2W$; stop light p: $4.5\pm 0.5W$.
Waterproof and Dustproof	IP67
Working temperature	-40°C ~ +65°C
Regulation	3C (GB 17509,GB 5920,GB 15235,GB 5920)
Corrosion resistance of surface Withstand voltage test	Salt spray test 126H
Reverse polarity protection	DC28V, 10min
Life span	$\geq 25000h$
Mounting method	Moungting with screws 4pcs M8*20bolt
Connection	Integrated DT Connector with open wires, L400 \pm 30mm, ending wih terminal connector DT04-6P.
Application	Engineering vehicle、 Truck tail light
Packaging	White color box, 1set/box, 10sets/carton (5 Pairs)