



CX series 2seat golf cart with golf rack /golf ball holder/ 10"street tire

Model No.: SH-CX020T			
<b>Power Supply</b>			
Motor	3KW AC motor		
Controller	48V275A Enpower controller (With function: Anti-running/slow down when release accelerator/ self-protection from under-voltage and over-current. )		
Battery	48V105AH lead-acid battery or lithium battery		
Charge Time	6-8h		
Charging input voltage	220V or 110V		
<b>Performance</b>			
Passenger capacity	2	Overall size	2350×1250×1880mm
Gross weight	530kgs	Carrying capacity	600kg
Maximum speed	28km/h	Climbing capacity	15%
Braking distance	≤3m	Minimum turning radius	3.5m
Maximum Noise	<50db		
<b>Chassis system</b>			
Chassis clearance	240mm	Wheelbase	1640mm
Front wheel distance	870mm	Rear wheel distance	970mm
Material of chassis	steel	Material of wheel hub	steel with cover
Size of tires	205/50-10		
Drive system	step-less speed control system		
Steering system	self-regulating pinion-and-rack steering gear		
Braking system	front disc brake and rear drum brake		
Front axle and suspension	not independent suspension, coil springs, telescopic hydraulic shock absorber		
Rear axle and suspension	integral floating rear axle, high-tensile steel spring, telescopic hydraulic shock absorber		
Seat	1 row of forward seat		
	double seat, leather fabric, high resilient PU, with armrest		
Frame	steel frame with PP plastic molding part		
Instrument panel	combination instrument		
	contain signal about forward and backward reversing, light, horn, and battery status		

Rearview mirror	manual outside rearview mirror
Light and signal	combination headlamp, combination tail lamp, turn signal, brake lamp, klaxon, etc
Switch	starting switch, light switch, forth and back gear switch and other rocker switch
Steering wheel	polyurethane (PU) steering wheel



CX series 2+2seat golf cart with golf ball holder/ 10"street tire

Model No.: SH-CX020TJ		
<b>Power Supply</b>		
Motor	3KW AC motor	
Controller	48V275A Enpower controller (With function: Anti-running/slow accelerator/ self-protection from under-voltage and over-current)	
Battery	48V100AH lead-acid battery ( 12V × 4pcs )	
Charge Time	6-8h	
Charging input voltage	220V or 110V	
<b>Performance</b>		
Passenger capacity	4	Overall size
Gross weight	550kgs	Carrying capacity
Maximum speed	28km/h	Climbing capacity
Braking distance	≤3m	Minimum turning radius
Maximum Noise	<50db	
<b>Chassis system</b>		
Chassis clearance	240mm	Wheelbase
Front wheel distance	870mm	Rear wheel distance
Material of chassis	steel	Material of wheel hub
Size of tires	205/50-10	
Drive system	step-less speed control system	
Steering system	self-regulating pinion-and-rack steering gear	
Braking system	front disc brake and rear drum brake	
Front axle and suspension	not independent suspension, coil springs, telescopic hydraulic	
Rear axle and suspension	integral floating rear axle, high-tensile steel spring, telescopic	
Seat	1 row of forward seat and 1 back seat	
	double seat, leather fabric, high resilient PU, with armrest	
Frame	steel frame with PP plastic molding part	
Instrument panel	combination instrument	

	contain signal about forward and backward reversing, light, h
Rearview mirror	manual outside rearview mirror
Light and signal	combination headlamp, combination tail lamp, turn signal, bra
Switch	starting switch, light switch, forth and back gear switch and o
Steering wheel	polyurethane (PU) steering wheel
FOB Ningbo price	<b>\$3100.00/pc</b>
<b>Optional parts</b>	
Option	Rise in Price
48V105AH Lithium battery	\$500.00



down when release  
ent. )

2650×1250×1880mm

600kg

15%

3.5m

1640mm

970mm

steel with cover

c shock absorber

; hydraulic shock absorber

orn, and battery status
ake lamp, klaxon, etc
ther rocker switch
Remark



CX series 4seat golf cart with golf rack /golf ball holder / 10"street tire

Model No.: SH-CX040T		
<b>Power Supply</b>		
Motor	3KW AC motor	
Controller	48V275A Enpower controller (With function: Anti-running/slow accelerator/ self-protection from under-voltage and over-current)	
Battery	48V100AH lead-acid battery ( 12V × 4pcs )	
Charge Time	6-8h	
Charging input voltage	220V or 110V	
<b>Performance</b>		
Passenger capacity	4	Overall size
Gross weight	580kgs	Carrying capacity
Maximum speed	28km/h	Climbing capacity
Braking distance	≤3m	Minimum turning radius
Maximum Noise	<50db	
<b>Chassis system</b>		
Chassis clearance	240mm	Wheelbase
Front wheel distance	870mm	Rear wheel distance
Material of chassis	steel	Material of wheel hub
Size of tires	205/50-10	
Drive system	step-less speed control system	
Steering system	self-regulating pinion-and-rack steering gear	
Braking system	front disc brake and rear drum brake	
Front axle and suspension	not independent suspension, coil springs, telescopic hydraulic	
Rear axle and suspension	integral floating rear axle, high-tensile steel spring, telescopic	
Seat	2 row of forward seat	
	double seat, leather fabric, high resilient PU, with armrest	
Frame	steel frame with PP plastic molding part	
Instrument panel	combination instrument	

	contain signal about forward and backward reversing, light, h
Rearview mirror	manual outside rearview mirror
Light and signal	combination headlamp, combination tail lamp, turn signal, bra
Switch	starting switch, light switch, forth and back gear switch and o
Steering wheel	polyurethane (PU) steering wheel
FOB Ningbo price	<b>\$3200.00/pc</b>
<b>Optional parts</b>	
Option	Rise in Price
48V105AH Lithium battery	\$500.00





ow down when release  
ent. )

3150\*1250\*1880mm

600kg

15%

4m

2390mm

970mm

steel with cover

c shock absorber

; hydraulic shock absorber

orn, and battery status
ake lamp, klaxon, etc
ther rocker switch
Remark