

## SPECIFICATION SHEET

MOTOTRBO™

XiR P8260/P8268/P8200/P8208

PORTABLE RADIOS



IDEAL COMMUNICATION SOLUTION FOR YOUR BUSINESS

# MOTOTRBO™

## XiR P8260/P8268/P8200/P8208 PORTABLE RADIOS

Motorola is a company of firsts with a rich heritage of innovation. We continue to invent what's next – connecting people, delivering mobility and making technology personal. Versatile and powerful, MOTOTRBO combines the best in two-way radio functionality with digital technology, making it the ideal communication solution for your business. You get enhanced features, increased capacity, integrated data applications, exceptional voice quality and extended battery performance. This means more productive employees and lower operating costs for your business.

- **Integrates Voice and Data** into one device to increase your operational efficiency and support integrated applications including MOTOTRBO Text Messaging Services. Also features an integrated GPS module for use with third-party location tracking applications.
- Uses Time-Division Multiple-Access (TDMA) digital technology to provide **Twice The Calling Capacity** (as compared to analog or FDMA radios) for the price of one frequency license. A second call doesn't require a second repeater, saving you equipment costs.
- In digital mode, provides **Clearer Voice Communications** throughout the coverage area, as compared to analog radios, rejecting static and noise.
- Offers **Enhanced Battery Life**. Digital TDMA two-way portable radios can operate up to 40 percent longer between recharges compared to typical analog radios.
- Meets **Demanding Specifications** – IP57 for submersibility in water (portable models), U.S. Military 810 C, D, E and F, and Motorola standards for durability and reliability.
- Is **Intrinsically Safe\***, when purchased and equipped with an FM battery, and can be used in locations where flammable gas, vapors or combustible dust may be present.
- Utilizes Motorola's **State-Of-The-Art IMPRES™ Technology** in batteries, chargers and audio accessories, providing longer talk time and clearer audio delivery.
- Features the **Transmit Interrupt Suite\*** – voice interrupt, remote voice dekey, emergency voice interrupt – to help prioritize critical communication exactly when needed.
- The **IP Site Connect\*** digital solution uses the Internet to extend coverage of your MOTOTRBO communication system to users anywhere in the world for dramatically improved customer service and increased productivity.
- **Capacity Plus\*** is a scalable, singlesite digital trunking solution that can expand the capacity of your MOTOTRBO communication to over a thousand radio users without adding new frequencies.
- **Motorola's Application Developer Program** enables the development of customized data applications that adapt MOTOTRBO radios to meet the unique needs of your business.

\*Optional feature, please indicate it when placing the radio order.

# MOTOTRBO™ PORTABLE RADIO

## GENERAL SPECIFICATIONS\*

	XiR P8260 Display Non GPS Model XiR P8268 Display GPS Model			XiR P8200 Non-Display Non-GPS Model XiR P8208 Non-Display GPS Model		
	350 MHz	UHF	VHF	350 MHz	UHF	VHF
Channel Capacity	1000			32		
Frequency	350-400 MHz	403-470 MHz / 450-512 MHz	136-174 MHz	350-400 MHz	403-470 MHz / 450-512 MHz	136-174 MHz
Dimension (HxWxT) w/ 1500 mAh Lilon Battery	131.5 x 63.5 x 35.2 mm			131.5 x 63.5 x 35.2 mm		
Weight (with 1500 mAh Lilon Battery)	360g (12.7 oz)			360g (12.7 oz)		
(with 2200 mAh Lilon Battery)	361g (12.8 oz)			361g (12.8 oz)		
(with 1400 mAh Lilon FM Battery)	370g (13 oz)			370g (13 oz)		
Power Supply	7.5V nominal			7.5V nominal		
FCC Description	—	AZ489FT4876 / AZ489FT4884	AZ489FT3815	—	AZ489FT4876 / AZ489FT4884	AZ489FT3815
Average battery life at 5/5/90 duty cycle with battery saver enabled in carrier squelch and transmitter in high power.						
IMPRES 1500 mAh Lilon Battery	Analog: 9 hrs Digital: 13 hrs			Analog: 9 hrs Digital: 13 hrs		
IMPRES 2200 mAh Lilon Battery	Analog: 13.5 hrs Digital: 19 hrs			Analog: 13.5 hrs Digital: 19 hrs		
IMPRES FM 1400 mAh Battery	Analog: 8.5 hrs Digital: 12 hrs			Analog: 8.5 hrs Digital: 12 hrs		

<b>Receiver</b>						
	350-400 MHz	403-470 MHz / 450-512 MHz	136-174 MHz	350-400 MHz	403-470 MHz / 450-512 MHz	136-174 MHz
Frequencies	350-400 MHz	403-470 MHz / 450-512 MHz	136-174 MHz	350-400 MHz	403-470 MHz / 450-512 MHz	136-174 MHz
Channel Spacing	12.5 kHz / 25 kHz			12.5 kHz / 25 kHz		
Frequency Stability	±/- 1.5 ppm (XiR P8260)			±/- 1.5 ppm (XiR P8200)		
(-30° C, +60° C, +25° C)	±/- 0.5 ppm (XiR P8268)			±/- 0.5 ppm (XiR P8208)		
Analog Sensitivity	0.35 uV (12 dB SINAD) 0.4 uV (20 dB SINAD) 0.22 uV (typical)			0.35 uV (12 dB SINAD) 0.4 uV (20 dB SINAD) 0.22 uV (typical)		
Digital Sensitivity	5% BER: 0.3 uV			5% BER: 0.3 uV		
Intermodulation						
TIA603C	70 dB			70 dB		
ETSI	65 dB			65 dB		
Adjacent Channel Selectivity	60 dB @ 12.5 kHz 70 dB @ 25 kHz			60 dB @ 12.5 kHz 70 dB @ 25 kHz		
Spurious Rejection	70 dB			70 dB		
Rated Audio	500 mW			500 mW		
Audio Distortion @ Rated Audio	3% (typical)			3% (typical)		
Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz			-40 dB @ 12.5 kHz -45 dB @ 25 kHz		
Audio Response	+1, -3 dB			+1, -3 dB		
Conducted Spurious Emission	-57 dBm			-57 dBm		

<b>Transmitter</b>						
	350-4000 MHz	403-470 MHz / 450-512 MHz	136-174 MHz	350-4000 MHz	403-470 MHz / 450-512 MHz	136-174 MHz
Frequencies	350-4000 MHz	403-470 MHz / 450-512 MHz	136-174 MHz	350-4000 MHz	403-470 MHz / 450-512 MHz	136-174 MHz
Channel Spacing	12.5 kHz / 25 kHz			12.5 kHz / 25 kHz		
Frequency Stability	±/- 1.5 ppm (XiR P8260)			±/- 1.5 ppm (XiR P8200)		
(-30° C, +60° C, +25° C)	±/- 0.5 ppm (XiR P8268)			±/- 0.5 ppm (XiR P8208)		
Power Output						
Low Power	1W	1W	1W	1W	1W	1W
High Power	4W	4W	5W	4W	4W	5W
Modulation Limiting	±/- 2.5 kHz @ 12.5 kHz ±/- 5.0 kHz @ 25 kHz			±/- 2.5 kHz @ 12.5 kHz ±/- 5.0 kHz @ 25 kHz		
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz			-40 dB @ 12.5 kHz -45 dB @ 25 kHz		
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz and < 4GHz			-36 dBm < 1 GHz -30 dBm > 1 GHz and < 4GHz		
Adjacent Channel Power	-60 dB @ 12.5 kHz -70 dB @ 25 kHz			-60 dB @ 12.5 kHz -70 dB @ 25 kHz		
Audio Response	+1, -3 dB			+1, -3 dB		
Audio Distortion	3%			3%		
FM Modulation	12.5 kHz : 11K0F3E 25 kHz : 16K0F3E			12.5 kHz : 11K0F3E 25 kHz : 16K0F3E		
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE			12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE		
Digital Vocoder Type	AMBE+2™			AMBE+2™		
Digital Protocol	ETSI-TS102 361-1			ETSI-TS102 361-1		

<b>GPS</b>	
Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)	
TTF (Time To First Fix) Cold Start	< 2 minutes
TTF (Time To First Fix) Hot Start	< 10 seconds
Horizontal Accuracy	< 10 meters

<b>Factory Mutual Approvals</b>	
MOTOTRBO XiR Portable series radios have been certified by FM Approvals in accordance with Canada and U.S. Codes as intrinsically safe for use in Class I, II, III, Division 1, Groups C,D,E,F,G, when properly equipped with a Motorola FM approved battery option. They are also approved for use in Class I, Division 2, Groups A, B, C, D.	

<b>Environmental Specifications</b>	
Operating Temperature	-30° C / +60° C
Storage Temperature	-40° C / +85° C
Thermal Shock	Per MIL-STD
Humidity	Per MIL-STD
ESD	IEC-801-2KV
Water Intrusion	IEC 60529 - IP57
Packaging Test	MIL-STD 810D and E

\* Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.  
Conforms to EC 1999/5/EC (R&TTE - Radio and Telecommunications Terminal Equipment) EN 300 088 EN 300 113

[www.motorolasolutions.com](http://www.motorolasolutions.com)

Motorola Solutions Singapore Pte Ltd 12 Ang Mo Kio Street 64, Ang Mo Kio Industrial Park 3, UE Biz Hub, Block A, Level 7 Singapore 569088

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2013 Motorola Solutions, Inc. All rights reserved.

AC3-04-29 Rev.6

