



# CPTL

Legal for trade price computing scale with pole





**Features:**

- Pricing, weighing
- Auto-power off, power on zero-tracking
- Low battery indicator, charging status indicator
- Piece price auto-average or manually entering piece price
- Accumulation memory
- Full tare
- Three LCD displays for weight, piece price and total price
- Customer display(dual)
- 10 x one-touch piece price memory keys (total 20 piece price memories)
- Adjustable feet and bubble level
- Materials:** ABS housing and 304 stainless steel platform
- Load cell:** ZEMIC L6D or equivalent (details on P138)

**Options:**

- Communication Port:** RS232 / RS485 / USB / BT
- Peripheral Devices:** Printer

**Approvals:**

-   
- FORCE No.:** 0200-NAWI-13975
- NTEP No.:** 14-041
- CE No.:** CE-238

**Applications:**

Retail, food industry, logistics, etc

**Specifications:**

Model	CPTL							
Accuracy	III							
Weighing Units	g, kg, lb							
Division	3,000							
Battery	6V/4AH battery up to 80 hours							
Power	Adapter 100V-240V, 12V/1A							
System	Metric system				Imperial system			
Capacity	1.5/3kg	3/6kg	6/15kg	15/30kg	3/6 lb	6/15 lb	15/30 lb	30/60 lb
Readability	0.5/1g	1/2g	2/5g	5/10g	0.001/0.002 lb	0.002/0.005 lb	0.005/0.01 lb	0.01/0.02 lb
Display	18mm LCD display, with LED backlight				¾" high LCD display, with LED backlit			
Operate Temp	-10 ° C to 40 ° C				14 ° F to 104 ° F			
Pan Size	225mm x 315mm x 15mm				8¾" W x 12½"L x ⅝"H			
Product Size	330mm x 345mm x 400mm				13" W x 13⅝"L x 15¾"H			
Packing Size	385mm x 445mm x 220mm				15" W x 17½"L x 8⅝"H			
Gross Weight	4.5 kg				10 lb			