

# CWT22

High-precision multi-function weighing scale





**Features:**

- Weighing, checkweighing, simple counting
- Auto-power off, power on zero-tracking
- Low battery indicator, charging status indicator
- Pre tare, full tare
- Accumulation memory
- Adjustable feet and bubble level
- Materials:** ABS housing and 304 stainless steel platform
- Load cell:** ZEMIC L6D or equivalent (*details on P138*)

**Applications:**

Retail, food industry, logistics, etc

**Options:**

- Communication Port:**  
RS232 / RS485 / USB / BT
- Peripheral Devices:**  
Printer / Alarm light

**Approvals:**

-   
- FORCE No.:** 0200-NAWI-13975
- NTEP No.:** 14-041
- CE No.:** CE-238

**Specifications:**

Model	CWT22							
Accuracy	III							
Weighing Units	g, kg, lb, oz, pcs, tj							
Division	3,000							
Battery	6V/4AH battery up to 80 hours							
Power	Adapter 100V-240V, 12V/1A							
System	Metric system				Imperial system			
Capacity	1.5/3kg	3/6kg	6/15kg	15/30kg	3/6 lb	6/15 lb	15/30 lb	30/60 lb
Readability	0.5/1g	1/2g	2/5g	5/10g	0.001/0.002 lb	0.002/0.005 lb	0.005/0.01 lb	0.01/0.02 lb
Display	30mm LCD display, with LED backlit				1¼" high LCD display, with LED backlit			
Operate Temp	-10 ° C to 40 ° C				14 ° F to 104 ° F			
Pan Size	225mm x 315mm x 15mm				8¾" W x 12½"L x 5/8"H			
Product Size	330mm x 345mm x 112mm				13" W x 13½"L x 4½"H			
Packing Size	380mm x 400mm x 150mm				15" W x 15¼"L x 6"H			
Gross Weight	4.2 kg				9.2 lb			