



Shenyang LongGreen T&S Co., LTD
Hothine:+086-24-25361668
No.108-2, Shenliao Road, Shenyang China

Technical Data Sheet

LongGreen 9346

Release agent used in the vulcanization process of rubber products

Product Description: milky white, sticky and liquid.

Use and operation:

LongGreen 9346 It can be sprayed, brushed or dipped. For dilution, use low hardness water, 1 portion of product plus 2 parts of water. A small test should be performed before production to determine the optimal concentration.

The user in touch into the eye will cause temporary pain, should be immediately cleaned with a lot of water;
Operation LongGreen 9346 protective glasses should be worn.

Recommended use:

The product can be used as release agent and lubricant, the product is efficient, stable, extremely used.
Rubber or plastic products (brake plate, crew head, plug, etc.) of the release agent;

-Lubricant for extruded rubber products such as conveyor belt and lubricant for the following textile process
-Lubrication of suture; production of socks and underwear; lubrication of suture needles; glass fiber mesh.

LongGreen 9346 The emulsion can also be used as a bright agent for cars and furniture, and its diluent can also be used for other purposes component.

LongGreen 9346 Medium viscosity and high brightness, less stains, if you need to mix, can be compatible with most other silicone emulsions.

particularanature: Stable tion stable (minimal oil at 54 ° C)

Freezing / thaw stability (six cycles)

Dilute stability

High mold release efficiency (less dosage)

No trace on the mold

Convenient application

The molded parts are not faded

Good surface wear resistance

Typical physicochemical properties:

surface: Creamy-white, sticky and liquid

proportion: 0.99 (g/ml, 25° C/15.6° C)

PH price: 8.5

Type of emulsifier: nonionic

Packaging and Storage:

50 kg 200 kg pack, plastic bucket

Unopened below 35° C, stored in a cool, dry place, with a shelf life of 18 months from the date of production.

The data in this information are accurate and credible. Because the use of the products is not under the supervision of Shenyang Longdelun Technology Co., Ltd., the company does not bear any legal responsibility for all the recommended projects. The data listed here can only be approximate, not as product specifications. Shenyang LongGreen Technology Co., Ltd. declares that: the reliability of the data is related to its use, because the company's products will be used together with other materials during the application process, so the company does not provide any guarantee.