



Main

Range of product	Modicon Quantum automation platform
Product or component type	Dc discrete output module
Discrete output number	96

Complementary

Group of channels	6 groups of 16
Discrete output logic	Negative logic (sink)
Addressing requirement	6 output words
Discrete output voltage	24 V DC
Output voltage limits	19.2...30 V
Voltage drop	0.4 V 0.5 A
Maximum load current	<= 0.5 A each point <= 19.2 A per module <= 3.2 A each group
Surge current	<= 2 A
Response time	<= 0.1 ms at state 0 to state 1 <= 0.1 ms at state 1 to state 0
Leakage current	1 mA 24 V
Short-circuit protection	With
Output overload protection	With
Load inductance	$\text{Inductance(H)} = 0.5 / ((\text{current(A)})^2 \times (\text{switching frequency(Hz)}))$ 0.5...4 Hz
Fault indication	Fault point Fault reporting Fault sensing Loss of field power
Isolation between channels and bus	500 Vrms DC for 1 minute
Power dissipation	7 W
Marking	CE
Local signalling	1 LED green bus communication is present (Active)

	1 LED red external fault detected (F) 96 LEDs green input status
Bus current requirement	<= 250 mA
Module format	Standard
Product weight	0.45 kg

Environment

Product certifications	C-Tick FM Class 1 Division 2 GOST RMRS
Standards	CSA C22.2 No 142 UL 508
Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m

Offer Sustainability


Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available End of life manual
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------

Racks for Modules Mounting


Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots

24 Vdc 6x16 Output Module

6 Groups of 16 Outputs A...F (6 x HE 10 Connectors)



140DDO36400 is replaced by:



Standard environment BMXDDO6402K

discrete output module M340 - 64 outputs - solid state - 24 V DC positive

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2021 | Not same dimensions/design - no equivalent 96-ch 24VDC source output (6X16)