

U^A

Dental Tech



Dental Handpiece — — X0

Product Features



Power Torque Head



Japanese Ceramic Bearing



Push Button



Patented Technology:
Bur Will Not Jump Out
When Rotating



Quiet Operation, Noise
Testing Is < 60dB



Holes Connection

Technical Data

Model	X0
Head	Torque
Air Pressure	0.25(Mpa)-0.3(Mpa)
Rotor Speed	300(krpm)-350(krpm)
Power	0.4(N)-0.45(N)/ 22W-24W
Water Flow	90(min/ml)-110(min/ml)
Water Pressure	0.2(Mpa)-0.23(Mpa)
Atomization Pressure	0.3(Mpa)-0.35(Mpa)
Noise	≤60dB
Bur Size	Φ 1.59mm-Φ1.60mm
Chuck Type	Push Botton
Spray	Single Spray
Coupling Type	2 Holes / 4 Holes
Bearing	Janpanese Cearmic Bearing
Material	Copper
Disinfection	135°C High Temperature And High Pressure Resistance
Cartridge	Exposed
OEM / ODM	Available
Patent	Bur Will Not Jump Out When Rotating
Warranty	Half Year

Dental Handpiece

— — X3



Technical Data

Model	X3
Head	Standard Head
Air Pressure	0.22(Mpa)-0.25(Mpa)
Rotor Speed	350(krpm)-400(krpm)
Power	0.4(N)-0.45(N)/ 22W-24W
Water Flow	90(min/ml)-110(min/ml)
Water Pressure	0.2(Mpa)-0.23(Mpa)
Atomization Pressure	0.3(Mpa)-0.35(Mpa)
Noise	≤60dB
Bur Size	Φ 1.59mm-Φ1.60mm
Chuck Type	Push Botton
Spray	Single Spray
Coupling Type	2 Holes / 4 Holes
Bearing	Japanese Cearmic Bearing
Material	Copper
Disinfection	135°C High Temperature And High Pressure Resistance
Cartridge	Exposed
OEM / ODM	Available
Patent	Bur Will Not Jump Out When Rotating
Warranty	Half Year

Product Features



Standard Head




Japanese Ceramic Bearing



Push Button



Patented Technology:
Bur Will Not Jump Out
When Rotating



Quiet Operation,Noise
Testing Is < 60dB



Holes Connection

Dental Handpiece — — Q0



Product Features



SMD Technology,
 1200 Times Under
 135°C Sterilization



Three Water Spray,
 High Cooling Effect



Integrated Torque Head

Technical Data

Model	Q0
Head	Torque, Integrated Torque Head
Air Pressure	0.25(Mpa)-0.3(Mpa)
Rotor Speed	300(krpm)-350(krpm)
Power	0.4(N)-0.45(N)/ 22W-24W
Water Flow	90(min/ml)-110(min/ml)
Water Pressure	0.2(Mpa)-0.23(Mpa)
Atomization Pressure	0.3(Mpa)-0.35(Mpa)
Noise	≤60dB
Bur Size	Φ 1.59mm-Φ1.60mm
Chuck Type	Push Botton
Light	SMD
Luminance	16000(LUX)-20000(LUX)
Temperature	5500(K)-6000(K)
Power	Self-generating LED
Bearing	Janpanese Cearmic Bearing
Spray	Triple Water Spray

Dental Handpiece

— — X4



Product Features



Using Specialized Bur
— 25mm



Air Is Exhausted Through
The Back Of The Handpiece



Standard Head

Technical Data

Model	X4
Head	Standard Head
Air Pressure	0.22(Mpa)-0.25(Mpa)
Rotor Speed	350(krpm)-400(krpm)
Power	0.35(N)-0.4(N)/ 20W
Water Flow	90(min/ml)-110(min/ml)
Water Pressure	0.2(Mpa)-0.23(Mpa)
Noise	≤60dB
Bur Size	Φ 1.59mm-Φ1.60mm
Chuck Type	Push Bottom
Spray	Single Spray
Coupling Type	2 Holes / 4 Holes
Bearing	Japanese Ceramic Bearing
Material	Copper
Weight	65.7g
Head Height (mm)	13.5
Head Diameter (mm)	11.2
Disinfection	135°C High Temperature And High Pressure Resistance
Cartridge	Cover
OEM / ODM	Available
Patent	Bur Will Not Jump Out When Rotating
Warranty	Half Year

Dental Handpiece

— — Q4



Technical Data

Model	Q4
Head	Standard Head
Air Pressure	0.22(Mpa)-0.25(Mpa)
Rotor Speed	350(krpm)-400(krpm)
Power	0.35(N)-0.4(N)/ 20W
Water Flow	90(min/ml)-110(min/ml)
Water Pressure	0.2(Mpa)-0.23(Mpa)
Noise	≤60dB
Chuck Type	Push Bottom
Spray	Single Spray
Light	LED
Coupling Type	2 Holes / 4 Holes
Bearing	Japanese Cearmic Bearing
Weight	65.7g
Head Height (mm)	13.5
Head Diameter (mm)	11.2
Disinfection	135°C High Temperature And High Pressure Resistance
Cartridge	Cover
OEM / ODM	Available
Patent	Bur Will Not Jump Out When Rotating
Warranty	Half Year

Product Features



Using Specialized Bur
—25mm



Air Is Exhausted Through
The Back Of The Handpiece



Standard Head



Unique 45 Degree Angled
With Led

1:5 Electric Contra Angle — — C7



Technical Data

Model	C7
Gear Ratio	1:5
Connector	E-type
Max Speed	200,000rpm
Noise	≤60 dB
Light	LED Fiber Optic
Power	Electric
Spray	Triple Water Spray
Chuck Type	Push Button
Bearing	Imported Bearing
OEM/ODM	Available
Warranty	1 Year
Weight	69.3g

Product Features

01

Cutting Faster: Large Torque, Faster Crown Breaking And Pulp Opening, Bur Will Not Get Stuck

02

Small Jitter: Swing Range ≤0.02mm, Grinding Surface Is Smooth And Clean Without Steps

03

Controllable Speed: Precisely Set The Best Speed , Avoiding Excessive Preparation And Correction Grinding, Ensure The Best Treatment Effect

04

Noise ≤ 60 dB: Healthier Dentists, More Comfortable Patients, Easier Diagnosis And Treatment Of Children's Teeth

05

Zero Return Suction: Effectively Prevent Cross-Infection , Make Doctors And Patients Safer



Dental Handpiece

— — CW0



Product Features

- 01 Chuck Type:Latch Type
- 02 External Water Irrigation
- 03 Water And Air Is Separately Divided
- 04 1 Year Warranty
- 05 Can Be Connected With Polishing Brush, Burs,Casting Ring,Grinding Head,Root Canal Needle And So On



Technical Data

Model	CW0
Air Pressure	0.25(Mpa)-0.3(Mpa)
Rotor Speed	18,000 - 21,000 rpm
Power	0.4(N)-0.45(N)/ 22W-24W
Water Flow	90(min/ml)-110(min/ml)
Water Pressure	198Kpa(2Kg)
Atomization Pressure	0.3(Mpa)-0.35(Mpa)
Noise	≤65dB
Bur Size	Φ2.334-Φ2.355(mm)
Chuck Type	Latch Type
Spray	Single Water Spray
Coupling Type	2 Holes / 4 Holes
Bearing	Imported Bearing
Material	Copper
Disinfection	135°C High Temperature And High Pressure Resistance
OEM / ODM	Available
Warranty	1 Year
Remark	1.External Water Irrigation 2.Can Be Connected With Polishing Brush,Burs, Casting Ring, Grinding Head, Root Canal Needle And So On

Dental Handpiece — — CN0



Product Features

- 01 Patent Technology:Self-lubricating Of Air Motor
- 02 Internal Water Irrigation
- 03 Chuck Type:Push Button
- 04 Imported Bearing
- 05 1 Year Warranty
- 06 Can Be Connected With Polishing Brush,Burs, Casting Ring,Grinding Head,Root Canal Needle And So On



Technical Data

Model	CN0
Air Pressure	0.25(Mpa)-0.3(Mpa)
Rotor Speed	18,000 - 21,000 rpm
Power	0.4(N)-0.45(N)/ 22W-24W
Water Flow	90(min/ml)-110(min/ml)
Water Pressure	198Kpa(2Kg)
Atomization Pressure	0.3(Mpa)-0.35(Mpa)
Noise	≤65dB
Bur Size	Φ2.334-Φ2.355(mm)
Chuck Type	Push Botton
Spray	Single Water Spray
Coupling Type	2 Holes / 4 Holes
Bearing	Imported Bearing
Material	Copper
Disinfection	135°C High Temperature And High Pressure Resistance
OEM / ODM	Available
Warranty	1 Year
Patent	Self-lubricating Of Air Motor
Remark	1.Internal Water Irrigation 2.Can Be Connected With Polishing Brush,Burs, Casting Ring, Grinding Head, Root Canal Needle And So On