

LZB-600-R30 Fully Automatic Brick Shape Vacuum Packing Machine

◆Applications

Used for the quantitative brick shape vacuum packaging in the industry of rice, grains, peanuts, and food etc.

◆ii. Technical parameters :

Model	LZB-600-R30
Weighing extent (kg)	0.5~5
Speed(bags/h)	500~600
Scale Interval	1
Precession grade	X(0.5)
Power	4N-AC 380V 50Hz、5.2KW
Power consumption	0.4~0.6MPa 24m ³ /h
Air , air consumption	3050×2700×2800

◆Basic configure :

NO.	Name	Supplier
1	Touch screen 10 "	Japan / Omron
2	Weighing controller	Canada/General
3	PLC	Japan / Omron
4	Switching Power Supply	Japan / Omron
5	Solid state relay	Japan / Omron
6	Intermediate relay	Japan / Omron
7	Load cell	USA/Celtron
8	Phase sequence protection relay	France / Schneider
9	Vacuum pump	Germany/ (LEYBOLD)
10	Cylinder	Japan /SMC
11	Solenoid valve	Japan /SMC
12	Linear Slides	Taiwan/ABBA
13	Miniature geared motors	TAIWAN/RUIYONG

●Functions and Features

Fully automatic

New generation of high-speed weighing control mode parameter automatic correction, adaptive weighing process various materials;

Omron touch screen, Omron PLC centralized control, intelligent control weighing, filling, six-sided plastic,

Vacuum, heat sealing, unloading bags, the whole process of transportation, real-time tracking system working state, friendly interface, easy to operate;

imported from Japan, SMC pneumatic components, high reliability and long service life;


imported from Germany, vacuum pumps, stable and reliable;

different packaging specifications to replace the mold is simple, fast, without any tools;

device with fault self-test function, maintenance is simple and convenient;

intelligent control information presentation system;

Automatic Bag interface reserved.




漳州佳龙科技股份有限公司				产品安装图			
标记	变更	分区	修改文件号	签名	年、月、日	数量	
						比例	
设计	徐阳	审核	工艺	批准		共 1 页 第 1 页	
						LZB-600-R30	

产品详细介绍

适配包装袋说明

佳龙公司 R 系列立体真空包装机适配包装说明：



备注：涉及到 R 系列产品装箱后需要机器人自动码垛的，所用箱子宽度范围需在 250mm-380mm 之间。