

High Speed Double hopper Packing Machine

DCS-25K-H10

Scope of application:

Quantitative packaging of granular materials in grain, sugar, food industries.

Technical Parameters

| Model specifications | DCS-25K-H10 |
|---------------------------------|---|
| Packing range (kg) | 5~25 |
| Packing speed (bag / h) | 900~1400 |
| Index value (g) | 2 |
| level of accuracy | X(0.5) |
| Power supply, power consumption | 4N-AC 380V 50Hz 1.1KW |
| Air source, gas consumption | 0.5~0.6MPa 13m ³ /h |
| Dimensions (L × W × H mm) | 2800×1050×3200 (high with small silo) |

Main configuration

| No. | Name | Main configuration |
|-----|---|--------------------------------|
| 1 | Weighing control instrument | United States / Mettler-Toledo |
| 2 | touch screen | Japan / Omron |
| 3 | Switching power supply | Japan / Omron |
| 4 | Buttons, knobs | Japan / Schneider |
| 5 | Load cell | United States / Mettler-Toledo |
| 6 | Limit switch | Japan / Omron |
| 7 | Pneumatic components (filters, solenoid | Taiwan / Airtec |
| 8 | cylinder | Taiwan / Airtec |
| 9 | Motor | Ningbo / Sanjing |



| | | |
|----|----------------------|---------------|
| 10 | Photoelectric switch | Japan / Omron |
|----|----------------------|---------------|

● Features

- Weighing and conveyor in one body make stable and reliable, no residue design.
- Large size touch screen is displayed and operated in a centralized manner, which is simple and convenient.
- One-key switch of packaging specifications, memory belt automatic lifting.
- Double feeding and double high-speed measuring mechanism, high-speed packing, greatly increasing output.
- Optional to add folding machine, the machine head can be moved laterally, it is easy to operate when it is equipped with or without the folding machine mechanism, it can cut the thread automatically, and automatically stitching machine oil feeding.
- Automatic error correction, over- and under-error alarms, and faults originate from diagnosis and other functions.
- ● RS232 / 485 serial port is reserved for data communication with peripheral management system.

◎ Picture for reference.



Scan the QRcode for video demo.