



多路换向阀 Multiple Directional Control Valves
型号Model: JRDF32H.2



产品特点Product Features

- | | |
|-------------------|--|
| 1、控制方式：手控 | 1.Control Mode:Control Manually |
| 2、回路形式：串联回路 | 2.Loop Form:Series Circuit |
| 3、密封性好 | 3.Good Sealing Performance |
| 4、溢流阀、过载阀等采用插装式结构 | 4.Overflow Valve And Overload Valve Adopt Plug-in Structure. |
| 5、结构紧凑、压力损失小 | 5.Compact Structure And Small Pressure Loss. |
| 6、通用性好，便于维修 | 6.Good Universality And Easy Maintenance. |

液压原理图Hydraulic Schematic Diagram



技术参数Specifications

概述Summary (JRDF32H.2)		
油口连接方式Oil Port Connection Mode		法兰连接Flanged Connection
控制方式Control Mode		压力控制Pressure Control
安装方式Installation Mode		见外形图See Outline Drawing.
通径Iatus Rectum	mm	32
液压Hydraulic Pressure		
公称流量Nominal Flow Rate	L/min	250
允许最大回油背压 Maximum Allowable Oil Return Back Pressure	bar	15
液压油温度范围 Hydraulic Oil Temperature Range	℃	-20 ~ +100
粘度范围Viscosity Range	m ² /s	10~460
油液允许的污染等级 Permissible Pollution Level Of Oil		-/19/16 (ISO4406:1999)
机械Machinery		
阀芯允许的最大操作力 Maximum Operating Force Allowed By Valve Core	N	300

产品外形图Product Outline Drawing

