

OPGW Suspension Clamp

Catalog Number		Diameter Range (mm)	Structural Reinforcement Rods					Outer rods				
Single	Double		Single Length (mm)	Double Length (mm)	Rod Dia. (mm)	Rods per set	Color Code	Single Length (mm)	Double Length (mm)	Rod Dia. (mm)	Rods per set	Color Code
OCL 0960 100	OCL 0960 100D	8.9-9.6	1676	2134	3.71	9	Blue	1067	1524	5.18	11	Blue
OCL 1010 100	OCL 1010 100D	9.7-10.1	1676	2134	3.71	9	Green	1067	1524	5.18	11	Green
OCL 1060 100	OCL 1060 100D	10.2-10.6	1676	2134	3.71	10	Yellow	1067	1524	5.18	11	Yellow
OCL 1110 100	OCL 1110 100D	10.7-11.1	1702	2134	3.71	10	Black	1067	1524	5.18	11	Black
OCL 1160 100	OCL 1160 100D	11.2-11.6	1727	2134	3.71	11	White	1092	1549	5.18	11	White
OCL 1170 100	OCL 1170 100D	11.7-11.7	1829	2286	4.24	10	Purple	1168	1626	6.35	10	Orange
OCL 1210 100	OCL 1210 100D	11.8-12.0	1829	2286	4.24	10	Purple	1168	1626	6.35	10	Purple
OCL 1270 100	OCL 1270 100D	12.1-12.7	1854	2286	3.71	11	Orange	1168	1626	6.35	10	Orange
OCL 1300 100	OCL 1300 100D	12.8-12.9	1930	2286	3.71	12	Red	1168	1626	6.35	10	Purple
OCL 1360 100	OCL 1360 100D	13.0-13.6	1930	2388	4.24	11	Blue	1245	1702	6.35	11	Blue
OCL 1420 100	OCL 1420 100D	13.7-14.1	1956	2388	4.24	11	Green	1245	1702	6.35	11	Green
OCL 1430 100	OCL 1430 100D	14.2-14.3	1956	2388	4.24	11	Green	1245	1702	6.35	11	Green
OCL 1450 100	OCL 1450 100	14.4-14.5	2007	2591	4.62	11	Black	1372	1930	6.35	12	Black
OCL 1520 100	OCL 1520 100D	14.6-15.1	2007	2591	4.62	11	Black	1372	1930	6.35	12	White
OCL 1580 100	OCL 1580 100D	15.2-15.8	2057	2591	4.62	11	Brown	1372	1930	6.35	12	Brown
OCL 1600 100	OCL 1600 100D	15.9-16.0	2388	3048	5.18	11	Red	1600	2261	7.87	11	Red
OCL 1690 100	OCL 1690 100D	16.1-16.9	2388	3048	5.18	11	Red	1600	2261	7.87	11	Blue
OCL 1730 100	OCL 1730 100D	17.0-17.3	2388	3048	5.18	11	Yellow	1600	2261	7.87	11	Green
OCL 1800 100	OCL 1800 100D	17.4-18.0	2388	3048	5.18	11	Yellow	1600	2261	7.87	11	Yellow
OCL 1850 100	OCL 1850 100D	18.1-18.4	2388	3048	5.18	12	White	1600	2261	7.87	12	Black
OCL 1890 100	OCL 1890 100D	18.5-18.8	2388	3048	5.18	12	White	1600	2261	7.87	12	White
OCL 1910 100	OCL 1910 100D	18.9-18.9	2388	3048	5.18	12	White	1600	2261	7.87	12	White
OCL 2000 100	OCL 2000 100D	19.0-19.9	2388	3048	5.18	12	Brown	1600	2261	7.87	12	Brown
OCL 2070 100	OCL 2070 100D	20.0-20.6	2540	3277	6.35	11	Green	1829	2565	9.27	11	Green
OCL 2150 100	OCL 2150 100D	20.7-21.4	2540	3277	6.35	11	Yellow	1829	2565	9.27	11	Yellow
OCL 2170 100	OCL 2170 100D	21.5-21.6	2540	3277	6.35	11	Blue	1829	2565	9.27	12	Blue
OCL 2270 100	OCL 2270 100D	21.7-22.6	2540	3353	6.35	12	Black	2032	2845	9.27	12	Black
OCL 2300 100	OCL 2300 100D	22.7-22.9	2540	3353	6.35	12	White	2032	2845	9.27	12	White
OCL 2330 100	OCL 2330 100D	23.0-23.2	2540	3353	6.35	12	Purple	2032	2845	9.27	12	Purple
OCL 2360 100	OCL 2360 100D	23.3-23.5	2540	3353	6.35	12	Brown	2032	2845	9.27	12	Brown
OCL 2390 100	OCL 2390 100D	23.6-23.9	2540	3353	6.35	12	Red	2032	2845	9.27	12	Red
OCL 2480 100	OCL 2480 100D	24.0-24.7	2540	3353	6.35	13	Orange	2032	2845	9.27	13	Orange

Catalog Number	Breaking strength (kN)	Weight (kg)	Dimension(mm)				
			A	B	C	D	E
VTCB-11-B	50	0.33	60	45	20	40	Ø16
VTCB-17-B	70	0.44	60	45	20	42	Ø16
VTCB-27-B	120	0.9	107	48	24	57	M16
VTCB-35-B	156	1.7	124	57	25.4	64	M18
VTCB-35-M	156	1.7	124	57	25.4	64	M16