

Preformed Ground Wire Tension Clamp (For Steel Wires)

Catalog Number	Standard Type DL/T763-2001	Conductor Type(GB1179-83) Aluminum Strand (LJ)	Length (mm)	Weight (kg)	Color Code
GEG-10025	NL-25/G	25	635	0.20	Yellow
GEG-10035	NL-35/G	35	711	0.30	Black
GEG-10050	NL-50/G	50	901	0.50	Orange
GEG-10056		55	889	0.53	Red
GEG-10070	NL-70/G	70	1016	0.80	Green
GEG-10080		80	1170	0.96	Black
GEG-10090		90	980	0.81	Red
GEG-10095	NL-95/G	95	1333	1.70	Orange
VBG-10100	NL-100/G	100	1333	1.70	Yellow
VBG-10120	NL-120/G	120	1460	2.20	Yellow

Preformed Ground Wire Tension Clamp (For Aluminum clad steel, ACSR)

Catalog Number	Diameter Range(mm)	ACSR	Length(mm)	Weight (kg)	Color Code
VAWDE-4102	4.42-4.60		445	0.1	Orange
VAWDE-4108	5.56-5.85		520	0.2	Green
VAWDE-4109	5.86-6.00		520	0.2	Orange
VAWDE-4110	6.61-6.28		610	0.2	Yellow
VAWDE-4111	6.29-6.56		545	0.2	Black
VAWDE-4112	6.57-6.84		550	0.2	Red
VAWDE-4113	6.85-7.12		600	0.2	Blue
VAWDE-4114	7.13-7.40		600	0.2	Green
VAWDE-4115	7.41-7.67		610	0.2	Yellow
VAWDE-4116	7.68-7.95		650	0.2	Black
VAWDE-4117	7.96-8.23		650	0.2	Red
VAWDE-4118	8.24-8.54		650	0.2	Green
VAWDE-4167	8.55-8.69		720	0.3	Orange
VAWDE-4119	8.70-9.02		725	0.3	Yellow
VAWDE-4120	9.03-9.25		775	0.5	Blue
VAWDE-4121	9.26-9.63		770	0.5	Red
VAWDE-4122	9.64-10.01		800	0.5	Orange
VAWDE-4123	10.02-10.39		840	0.6	Yellow
VAWDE-4124	10.40-10.82		850	0.7	Black
VAWDE-4125	10.83-11.23		900	0.7	Green

VAWDE-4126	11.24-11.66	50/30	940	1.0	Yellow
VAWDE-4127	11.67-12.04		950	0.9	Red
VAWDE-4128	12.05-12.55		980	1.0	Blue
VAWDE-4129	12.56-13.08		1080	1.4	Red
VBG-4170	13.09-13.61	70/40	1190	1.5	Red
VBG-4171	13.62-14.10		1220	1.5	Yellow
VBG-4172	14.11-14.48		1250	1.5	Blue
VBG-4173	14.49-15.01		1270	1.5	Orange
VBG-4174	15.02-15.54		1270	1.5	Green
VBG-4175	15.55-16.13	95/55	1370	1.5	Yellow
VBG-4176	16.14-16.79		1420	1.5	Black
VBG-4177	16.80-17.42		1500	2.3	Blue
VBG-4178	17.43-18.08	120/70	1550	3.0	Red
VBG-4179	18.09-18.82		1600	3.2	Black
VBG-4180	18.83-19.61		1800	3.7	Yellow