



Dual-Port Pedestal AC Charger

Commercial EV Charger Suitable for NA



- Ambient Lighting
- Convenient Payment Credit Card, No Hassle
- Status Indicator Lights
- Illuminated Logo Design
- Motion-Sensing Night Light
- Optional Cable Management System
- Optional Security Camera

Easy Options

									MORE+.....
Ethernet(LAN)	Bluetooth	Wi-Fi	4G	OCPP1.6J	RFID	Credit Card	Exact Billing	ISO15118	

Up to 45% Saving
TAA/BABA compliant supply solutions, avoid high tariffs.



DATASHEET

Model Number	CNAC-48A*2-RGWB-WH06	CNAC-80A*2-RGWB-WH06
Product Type	All in one AC Charging Station	
Input Voltage	208/240V AC, Single-phase	
Input Frequency	50/60 Hz	
Output Voltage	208/240V AC	
Output Current	48A Max ×2	80A Max ×2
Maximum Power Output	11.5kW ×2	19.2kW ×2
Input Wire	Hardwired	
Charging Connector Type	2×SAE J1772(Default), NACS Tesla(Optional)	
Cable Length	Cable Management,2×18FT/5.5m Standard (2×25FT/7.5m Optional)	
Charging Modes	Mode3	
Charging Protocols	OCPP 1.6J	
Dimensions (H × W × D)	440mm*420mm*1800mm(17.3*16.5*70.9inch)	
Weight	59.1lbs(26.8kg)	71.9lbs(32.6kg)
Enclosure Rating	NEMA Type3, IK08	
Operating Temperature	-30°C to 50°C(-22°F to 122°F)	
Operating Humidity	<95% Non-condensing	
Altitude	Up to 2000m	
Protection Function	Undercurrent Protection, Overcurrent Protection, Undervoltage Protection, Overvoltage Protection, Short Circuit Protection, Residual Current Device, Over Temperature Protection, Surge Protection, Ground Fault Protection, Control Pilot Fault Protection, Leakage Protection	
Emergency Stop	E-stop Button	
Communication Interface	10.1Inch Touch Screen,WIFI/4G	
Control Method	RFID/NFC, POS, OCPP Platform	
Mounting Type	Floor Standing Installation	
Compliance Standards	CSA, FCC, Energy Star, NTEP compliance, ISO15118 compliance	
Standards	NEC625, UL817, UL991, UL2231, UL2251, UL2594, OCPP1.6J Compliance	
Warranty Period	2 years	