

HYSTEROSCOPES OES 4000

Slim outer Diameter, excellent Image Quality.



- · Perfect flow characteristics
- Scratch-proof sapphire glass front window
- · Ultra-wide field of view












Complete line of OES 4000 stainless steal sheaths

The 3 mm **standard** system provides you with the hysteroscope of choice, an optical quality close to the 4 mm telescope, great ease of use. For extensive therapeutic procedures in the operation room we recommend our 4 mm **advanced** system. The use of high value materials and a unique design secure longterm durability and Olympus superior autoclavability.

Standard System



Sheaths	;
A4770	Sheath, single flow, 4 mm
A4771	Sheath*, continuous flow, 4.5 mm, 3 Fr. channel
A4772	Sheath*, continuous flow, 5.5 mm, 5 Fr. channel
A4773	Sheath*, continuous flow, 6.5 mm, 7 Fr. channel

^{*} For sealing caps and surgical instruments (HYS+), see our catalog or contact your local representative.

Advanced System

4 mm Telescope					
A22005A	Telescope, 4 mm, 30° direction of view, wide	autoclave autoclavable	WA03300A	Light guide cable, 2.8 mm, plug type	
	Delivery include tray.	des an instrument			

Sheaths and Working Inserts				
A4760	Sheath, single flow, 5 mm			
A4761	Sheath*, continuous flow, 5.5 mm, 3 Fr. channel			
A47610A	Sheath*, continuous flow, 6.5 mm, 5 Fr. channel			
A4767	Obturator, standard, for A4760, A4761, A47610A			
A4763	Sheath, 8 mm			
A4766	Obturator, 8 mm, optical, for A4763			
A4764	Working insert*, with ramp, 7 Fr. channel			

Specifications, design, and accessories are subject to change without any notice or obligation on the part of the manufacturer.

