



## Fire Alarm Cable

### 1.25mm<sup>2</sup>/2 Cores

### Technical Datasheet

### Applications

Fire Protective Signaling Circuits, Smoke detectors, Strobes/Sirens, Pull stations, Voice communications, Burglar alarms, Audio, control, initiating & notification circuits, Microprocessor/Addressable Controlled Systems

Physical Characteristics	Certifications
Conductor: 16/0.32mm Stranded Tinned Copper	ISO9001, ISO14001, OHSAS 18001
Number of Insulation: 2	UL 13, UL 1424, UL444, NEC725
Insulation: 2.70mm Flame-Retardant & RoHS Compliant PVC	UL listed Type: CMR, CL3R, CL2R (UL 1666) CM, CL3, CL2 (UL 1685)
Insulation Color Code: 1. Red 2. Black	ETL listed Type: CMR, CL3R, CL2R (UL 1666) CM, CL3, CL2 (UL 1685)
Jacket: Flame-Retardant & RoHS Compliant PVC	RoHS / REACH Compliant
Jacket Color Code: Grey	CE CPR E class
Nominal Cable Diameter: 7.9mm	AS/NZS 5000.2.2006
Temperature Rating (°C):	<b>Electrical Characteristics</b>
Installation: 0 to +60	Operating Voltage: 750 Volts Max
Storage & Operation: -20 to +75	DC Resistance: Ohms/m @ +20 °C

**Zhejiang Tianjie Industrial Corporation**

T: +86 (0)571 2365 6065 F: +86 (0)571 2365 6098

W: [www.tianjiec corp.com](http://www.tianjiec corp.com) [www.tian-jie.com](http://www.tian-jie.com)

