## Flat Roof Mount System I





## **Features:**


- 1. Adjustable tilt angle per different request;
- 2. Highly pre-assembled parts on factory can
- save installation time on site and labor cost;
- 3. Simple and fast installation;
- 4. Hardware included;
- 5. Customized request can accept.

\_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_

## **Technical information**

Application: Commercial & residential area Max Wind Speed: 60m/s Material: Aluminum 6005-T5

Fixed Triangle Mount				
Item No.	Description	Length of Back Tilt		
MG-FT-RM-15	Fixed Triangle Mount, Tilt angle 15°	405mm		
MG-FT-RM-20	Fixed Triangle Mount, Tilt angle 20°	505mm		
MG-FT-RM-30	Fixed Triangle Mount, Tilt angle 30°	705mm		



## **Fixed Triangle Mount**

Length: 1335mm	Adjustable Triangle Mount		
Length. 1555hill	Item No.	Description	Adjustable Angle Range
Length: 1380mm	MG-AT-RM-10/15	Adjustable Triangle Mount, 10/15°	10~15°
· · ·	MG-AT-RM-15/30	Adjustable Triangle Mount, 15/30°	15~30°
Adjustable Triangle Mount		15/50	<u> </u>