



300V 5A 20-18AWG 1.5mm<sup>2</sup>

Poles: 1P-XXP

Pitch: 5.0mm (.197")/5.08mm (.200")

Materials

Housing: PA66(UL 94V-0)

Solder Pin: Brass, Tin Plated

Clamping: stainless steel

|                              |                |               |                |                           |       |
|------------------------------|----------------|---------------|----------------|---------------------------|-------|
| 设计/Designed by               | 绘图/Drawing by  | 审核/Checked by | 批准/Approved by | 未注公差<br>General Tolerance |       |
|                              |                |               |                | Z                         | Z'    |
|                              |                |               |                | ±0.2                      | ±0°   |
|                              |                |               |                | .X                        | .X'   |
|                              |                |               |                | ±0.1                      | ±0°   |
|                              |                |               |                | .XX                       | .XX'  |
|                              |                |               |                | ±0.05                     | ±0.5° |
|                              |                |               |                | .XXX                      | ±0.01 |
|                              |                |               |                | ±0.01                     |       |
| 图名/Title name                | 文件编号/Title No. | 备注/Remark     | 单位/Units:      | mm                        |       |
| XY119A-5.0                   |                |               |                |                           |       |
| XY119B-5.08                  | 页序/Sheet       |               |                |                           |       |
| XINLAIYA ELECTRONIC CO., LTD |                |               |                |                           |       |

**X** 新莱亚电子  
XINLAIYA ELECTRONIC CO., LTD