



300V 15A  
 Piles: (2-24P)  
 Pitch: 5.0mm (.197")/5.08mm (.200")

**Material**

Housing: PA66 (UL 94V-0)  
 Pin header: Brass, Tin Plated

序号/Revno. 更改记录/Revision note 签名/Signature 日期/Datce

|                |  |               |  |               |  |                |  |                           |  |
|----------------|--|---------------|--|---------------|--|----------------|--|---------------------------|--|
| 设计/Designed by |  | 绘图/Drawing by |  | 审核/Checked by |  | 批准/Approved by |  | 未注公差<br>General Tolerance |  |
|                |  |               |  |               |  |                |  | X. ±0.2 X.° ±2°           |  |
|                |  |               |  |               |  |                |  | .X ±0.1 .X° ±1°           |  |
|                |  |               |  |               |  |                |  | .XX ±0.05 .XX° ±0.5°      |  |
|                |  |               |  |               |  |                |  | .xxx ±0.01                |  |
| 图名/File name   |  | 文件编号/File No. |  | 页序/Sheet      |  |                |  |                           |  |
| XY2505VC-5.0   |  |               |  |               |  |                |  |                           |  |
| 备注/Remark      |  |               |  |               |  |                |  |                           |  |
|                |  |               |  |               |  |                |  | 单位/Units: mm              |  |

