



**Specifications:**  
 Contact Resistance: 30mΩ max. at dc 100 mA  
 Insulator Resistance: 1000MΩ min. at DC 500V  
 Current Rating: 5AMP  
 Dielectric Withstanding Voltage: AC 1000V For 1 minute  
 Operating Temperature: -55°C—+105°C  
 Contact: Brass  
 Housing: PBT 830% Glass Fiber (UL 94V-0)

Position	A	B	C
9	24.99	30.81	19.36
15	33.32	39.20	27.64
25	47.04	53.10	41.08
37	63.50	69.50	57.38

- 要求:**
1. 外壳无明显起皮、杂色、生锈, 断面毛边不超过0.05mm.
  2. 端子无松动, 且整排端子成一直线, 端子之间相互平行, 塑件无明显错位.
  3. 吻合要紧密, 外壳接合处无明显缝隙, 且吻合处平滑.

设计/Designed by: 绘图/Drawn by: 审核/Checked by: 批准/Approved by: 本图公差 General Tolerance

**新莱亚电子**  
 XINLIYA ELECTRONIC CO., LTD

图名/Title	文件编号/File No.	x. ±0.2	x. ±2°
100M		.x ±0.1	.x° ±1°
页序/Sheet		.xx ±0.05	.xx° ±0.5°
备注/Remark		.xxx ±0.01	