



Position	A	B	C
9	24.99	30.81	19.36
15	33.32	39.20	27.64
25	47.04	53.10	41.08
37	63.50	69.50	57.38

Specifications:  
 Contact Resistance: 30mΩ max.at dc 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 5AMP  
 Dielectric Withstanding Voltage: AC 1000V For 1 minute  
 Operating Temperature: -55℃--+105℃  
 Contact: Brass  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

- 要求:
1. 铁壳无明显起皮、杂色、生锈, 断面毛边不超过0.05mm.
  2. 端子无松动, 且整排端子成一直线, 端子之间相互平行, 塑件无明显错位.
  3. 铆合要紧密, 铁壳接合处无明显缝隙, 且铆合处平滑.

序号/revno. 更改记录/revision record 签名/signature 日期/date

设计/modified by 绘图/drawing by 审核/checked by 批准/approved by 本图公差 General Tolerance

图名/title 零件编号/part no. x. ±0.2 x.° ±2°  
 .x ±0.1 .x° ±1°

100F 页序/sheet .xxx ±0.05 .xxx ±0.5°  
 .xxx ±0.01

备注/reemark 单位/unit: mm



新莱亚电子  
 XINLEIYA ELECTRONIC CO., LTD