



Specifications:
 Contact Resistance: 30mΩ max.at DC 100 mA
 Insulator Resistance: 1000MΩ min.at DC 500V
 Current Rating: 1AMP

Dielectric Withstanding Voltage: AC 500V For 1 minute
 Operating Temperature: -55 ℃-- +105 ℃
 Contact: Phosphor bronze
 Housing: PBT &30% Glass Fiber(UL 94V-0)

Position	Dimension			
	A	B	C	D
6	7.52	5.08	10.16	7.62
8	10.16	7.62	10.16	7.62
14	17.82	15.24	10.16	7.62
16	20.32	17.78	10.16	7.62
18	22.86	20.32	10.16	7.62
20	25.40	22.86	10.16	7.62
24	30.48	27.94	10.16	7.62
24	30.48	27.94	17.78	15.24
28	35.56	33.02	10.16	7.62
28	35.56	33.02	17.78	15.24
32	40.64	38.10	17.78	15.24
40	50.80	48.26	17.78	15.24
42	53.21	50.80	17.78	15.24

- 要求:
1. 塑料件无裂痕。
 2. 整排端子成一直线，相邻端子之间相互平行。

设计/created by	绘图/drawing by	审核/checked by	批准/approved by	备注/remark
图名/title	零件编号/part no.	名称/revision	页序/page	单位/unit(s)
1215				
公差/公差		General Tolerance		
x. ±0.2		x. ±0.2		
.x ±0.1		.x ±0.1		
.xx ±0.05		.xx ±0.05		
.xxx ±0.01		.xxx ±0.01		