



Specifications:

Contact Resistance: 30mΩ max.at DC  
 100 mA  
 Insulator Resistance: 1000MΩmin.at DC  
 500V  
 Current Rating: 1AMP

Dielectric Withstanding  
 Voltage: AC 1000V For 1 minute  
 Operating Temperature: -55℃--+105℃  
 Contact: Brass  
 Housing: PBT &30% Glass Fiber (UL  
 94V-0)

Position	A	B	C
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.78	48.58	40.64
40	58.40	56.20	48.26
50	71.10	68.90	60.96
60	83.80	81.60	73.66
64	88.88	86.68	78.74

序号/revise: 更改记录/revision record 签名/signature 日期/date

设计/modified by: 绘图/drawing by: 审核/checked by: 批准/approved by: 备注/remark



图名/drawing title: 1184-Straight needle  
 零件编号/part no.:  
 页序/page: 单位/unit: 数量/quantity:

公差/General Tolerance:  
 1. ±0.2  
 2. ±0.1  
 3. ±0.05  
 4. ±0.01