



Specifications:

Contact Resistance: 30mΩ max. at DC 100 mA

Insulator Resistance: 1000MΩmin. at DC 500V

Current Rating: 1AMP

Dielectric Withstanding

Voltage: AC 1000V For 1 minute

Operating Temperature: -55°C- +105°C

Contact: Brass

Housing: PBT 830% Glass Fiber (UL 94V-0)

Position	A	B	C
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.78	48.58	40.64
40	58.40	56.20	48.26
50	71.10	68.90	60.96
60	83.80	81.60	73.66
64	89.88	86.68	78.74

Design/modified by: 绘图/drawing by: 审核/checked by: 批准/approved by: 本图公差

General Tolerance: X: ±0.2 X*: ±2%
 Y: ±0.1 Y*: ±1%
 Z: ±0.05 Z*: ±0.5%
 XXX: ±0.01

图名/Title: 118A-beat needle 零件编号/Part No. 页序/Sheet: 备注/Remark: 单位/units: 数量

新莱亚电子 XINLAIYA ELECTRONIC CO., LTD

序号/revise: 更改记录/revision record 签名/signature 日期/date