



Specifications:
 Contact Resistance: 30mΩ max.at DC 100 mA
 Insulator Resistance:1000MΩ min.at DC 500V
 Current Rating: 1AMP

Dielectric Withstanding
 Voltage: AC 500V For 1 minute
 Operating Temperature: -55°C--+105°C
 Contact: Brass
 Housing: PBT &30% Glass Fiber(UL 94V-0)

Position	A	B	C	D
10	32.00	10.16	21.84	17.96
12	34.54	12.70	24.38	20.50
14	37.08	15.24	26.92	23.04
16	39.62	17.78	29.46	25.58
20	44.70	22.86	34.54	30.66
26	52.32	30.48	42.16	38.28
30	57.40	35.56	47.24	43.36
34	62.48	40.64	52.32	48.44
40	70.10	48.26	59.94	56.60
50	82.80	60.96	72.64	68.76
60	95.50	73.66	85.34	81.46
64	100.58	78.74	90.42	86.54

Design/checked by: 绘图/drawing by: 审核/checked by: 批准/approved by: 本图公差 General Tolerance

图名/Title: 119-bent needle 零件编号/Part No. X. ±0.2 X. ±2° X. ±0.1 .X. ±1° .XX ±0.05 .XX ±0.5° .XXX ±0.01

页序/Sheet: 备注/Remark: 单位/units: 张数

新莱亚电子 XINLAIYA ELECTRONIC CO., LTD

序号/revise: 更改记录/revision record 签名/signature 日期/date