



**Specification**

1. Insulation Resistance:  
1000 Megohms min.
2. Withstand Voltage:  
1000V, AC/ minute
3. Durability:  
600 mating circles min.
4. Tolerances unless otherwise specified:  
0~10: ±0.1; 10~20: ±0.15;  
20~30: ±0.2
5. Selective Gold-plating:  
(3; 6; 15; 30; 50 ) micro inch

设计/designed by	绘图/drawing by	审核/checked by	批准/approved by	备注/remark											
				图名/file name	文件编号/file No.										
				XYA057	页序/sheet										
单位/units: mm				<table border="1"> <tr> <th colspan="2">公差</th> </tr> <tr> <td>X. ±0.2</td> <td>X. ±2°</td> </tr> <tr> <td>.X ±0.1</td> <td>.X ±1°</td> </tr> <tr> <td>.XX ±0.05</td> <td>.XX ±0.5°</td> </tr> <tr> <td>.XXX ±0.01</td> <td></td> </tr> </table>		公差		X. ±0.2	X. ±2°	.X ±0.1	.X ±1°	.XX ±0.05	.XX ±0.5°	.XXX ±0.01	
公差															
X. ±0.2	X. ±2°														
.X ±0.1	.X ±1°														
.XX ±0.05	.XX ±0.5°														
.XXX ±0.01															