



福建泉州市劲力工程机械有限公司

Fujian Quanzhou Jinli Engineering & Machinery Co., Ltd

JG230S 轮胎式四瓣夹抓装机

SPECIFICATION OF JG230S GRAPPLE EXCAVATOR

工作范围Range of Operation	
动臂长度 Boom length	9000mm
斗臂长度 Arm length	4000mm
卸载高度 Maximum Dumping Height	4500~10500mm
最远装夹距离 Farthest Grabing Distance	5500~12500mm
驾驶室可提升高度 Max. lifting height of cab	1800~2500mm
后端回转半径 Back-end radius of gyration	3500mm
外型尺寸Dimensions	
(总长*总宽*总高) 运输状态 (Length*width*height) Transport Dimensions	11500*3000*3500mm
轴距 Axle base	3300mm
轮距 (前/后) Wheel base (front/rear)	1930mm
配重离地间隙 Ground clearance of counterweight	1350mm
最小离地间隙 Min ground clearance	400mm
四瓣夹参数SPECIFICATION OF ORANGE PEEL GRAPPLE	
旋转角度 Angle of rotation	360°
夹具总重量 Weight of Grab	760Kg
最大开口 Max. Opening Width of Grab	1530mm
闭合直径 Closing diam	880mm
技术性能参数Tech performance and specification	
旋转角度 Angle of rotation	360°
整机重量 Machine weight	25000kg
发动机型号 Engine model	康明斯 (国 II) Cummins (National Stage II)
额定功率 Rated Power	133KW
额定转速 Rated Speed	2200r/min
挖掘斗容 Volume of bucket	1.1m ³
液压系统工作压力 Hydraulic system working pressure	32Mpa
液压系统流量 Hydranlic system flow	450L/min
最高行驶速度 Walking speed	25km/h
燃油量 Fqt Fuel Quantity	≥12L/h
注: 产品参数以实物为准, 解释权和最终解释权归公司所有。 Note: The product parameters are based on the actual product, and the right of interpretation and final interpretation belong to the company.	