

KN-4004

UV Phototherapy



KN-4004A/B/AB



KN-4004A/B/AB

KN-4004A/B/AB: 600mm×140mm×1850mm (L×W×H)
 KN-4004A/B/AB: 600mm×80mm×1850mm (L×W×H)

Function introduction

- Stable and long usage life Philips special UV lamps as light source
- 8 pieces UV lamps of various combinations
- High-grade professional system design Color LCD, Chinese and English interface
- Multi-user management, accumulation of working time, and display of time countdown and dose countdown simultaneously
- Encoder technology makes operation more convenient and efficient
- Microcomputer controls dose and time to guarantee the treatment accuracy
- PUVA and NBUBV work separately or simultaneously
- High intensity UV light output reduces the treatment times but with obvious effect
- Hardware and software double monitoring function ensure the patients' safety
- Unique anti-interference technology ensures the normal use of equipment in strong magnetic field
- Case management function

Specification

KN-4004A	8×100W—UVA
KN-4004B	8×100W—NBUBV
KN-4004AB	4×100W—UVA, 4×100W—NBUBV
KN-4004A:	4×100W—UVA
KN-4004B:	4×100W—NBUBV
KN-4004AB:	2×100W—UVA, 2×100W—NBUBV

UV lamp parameter

TL100W/10-R	350-400nm
TL100W/01	311-312nm
TL100W/09	320-400nm